



## COMPOSITE VESSELS

### PROVEN PERFORMANCE IN COMMERCIAL AND INDUSTRIAL APPLICATIONS



The non-corrosive, cost-effective solution for commercial/industrial water treatment and storage. Pentair® Composite Vessels offer fiberglass construction for outstanding performance and durability in harsh chemical environments. Available in capacities up to 900 gallons, composite vessels are available with a variety of different configurations.

#### FEATURES/BENEFITS

100% composite fiberglass construction  
Outstanding performance and durability  
Seamless design prevents from leakage  
Absolutely will not-and cannot-rust  
Factory-backed five-year warranty

#### MATERIAL OF CONSTRUCTION

Polyethylene Inner shell  
Opening in various options:  
4 in. threaded,  
6 in. flanged.

#### APPLICATIONS

Commercial/industrial softening  
Commercial/industrial filtration

#### OPERATING PARAMETERS

Maximum operating temperature-  
Thread inlet tank 49°C (120°F)  
Flange inlet tank 65°C (150°F)  
Maximum vacuum: 127mmHg (5"Hg)

#### PENTAIR DESIGN PARAMETERS

Safety factor - 4:1  
Minimum burst at 600 psi  
Tested to 250,000 cycles without leakage

#### NSF/ANSI DESIGN PARAMETERS

Safety factor - 4:1  
Minimum burst at 600 psi  
Tested to 100,000 cycles without leakage

#### COLOR OPTIONS

GR - Gray NA - Natural  
BL - Blue BK - Black



This pressure vessel has been tested and certified by WOA according to NSF/ANSI Std. 61 Section 8 and Std. 372 for lead free compliance.

# SPECIFICATIONS FOR PE LINER TANKS

Tank Dia.	Tank Size		Opening		Total Height		Dia. mm	Capacity		Base
	in.	mm.	Top	Bottom	(LA) mm.	(LB) mm.		Gal.	Litre	
24 in.	24X72	610x1829	4"-8UN	\	1880	1743	613	119		SMC
	24x72	610x1829	4"-8UN	4"-8UN	2090	1764	625	119		TRIPOD
30 in.	30X72	762x1829	4"-8UN	\	2003	1775	764	187		SMC
	30X72	762x1829	4"-8UN	4"-8UN	2105	1772	764	187		TRIPOD
36 in.	36X72	914x1829	4"-8UN	\	2042	1776	914	264		SMC
	36X72	914x1829	4"-8UN	4"-8UN	2160	1791	914	264		TRIPOD
	36X72	914x1829	6" FLG	\	2090	1825	917	264		SMC
	36X72	914x1829		6" FLG	2210	1922	917	264		TRIPOD
42 in.	42X72	1067x1829		6" FLG	2289	1854	1073	345		TRIPOD
48 in.	48X72	1219x1829		6" FLG	2335	1932	1226	463		TRIPOD
63 in.	63X67	1600x1702		6" FLG	2068	1704	1626	600		TRIPOD
	63X86	1600x2184		6" FLG	2513	2164	1626	900		TRIPOD

\*Measurements are subject to change without notice and are for reference only.

\*Please refer the individual drawing for dimension, volumes and weight etc.

**NOTE:** Flexible connections must be installed between hard piping and tank opening. Failure to install flex connection properly with the vessel will void the warranty.

**NOTE:** An adequate vacuum breaker must be installed if negative pressure exceed 127mmHg (5" Hg) inside.

